## **Shamir Product Family**

Shamir Piccolo®

Shamir Genesis®

To view a specific product material availability, select the product name from the list below.

To return to this page, click on the Shamir logo located in the bottom right-hand corner of the page you are on.

Everyday> Progressive	Performance> Sport	Occupation
Shamir Autograph III®	Shamir Golf™	Shamir Autograph II - Office™
Shamir Autograph II®	Shamir Autograph II - Attitude™	Shamir Relax™
Shamir InTouch™	Shamir Attitude™	Shamir Office™
Shamir Spectrum™	_	
Shamir Element™		
Shamir FirstPAL™		
Shamir Creation®		

Everyday> Single Vision	Everyday> Single Vision
Shamir Autograph II - Single Vision™	Shamir Golf - Single Vision™
Shamir Spectrum - Single Vision™	Shamir Autograph II - Attitude Single Vision™
Shamir Single Vision™	



## Shamir Autograph III®

#### PRESCRIPTOR ORDER CODE:

AUTOGRAPH III 11 AUTOGRAPH III 18 AUTOGRAPH III 13 AUTOGRAPH III VARIABLE AUTOGRAPH III 15

#### PRODUCT FEATURES:

- ☐ CONVENTIONAL SV 💢 NATURAL POSTURE™

- Recommended min fitting heights are 11mm, 13mm, 15mm and 18mm
- Variable 11mm and up
- Prism to 4.00 Diopters

	TREATMENT				COATING	
CR-39	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00		-12.25 to +6.00	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00		+0.75 to +4.00	
CYLINDER	to -6.00	to -6.00	to -6.00		to -6.00	
OTHER		Gray/Brown	Gray		Gray/Brown/G-15	
INVISIBLE MARKINGS - 11mm	15 250 A <sup>11</sup>	TR 250 A11	X5 250 A <sub>11</sub>		97 PZ 250 A <sup>11</sup>	Clear, Transiti@ns <sup>-</sup> and
INVISIBLE MARKINGS - 13mm	15 250 A <sub>13</sub>	TR 250 A <sub>3</sub> <sup>13</sup>	X5 X5 250 A <sup>13</sup>		PZ 250 A <sub>3</sub> <sup>13</sup>	Polarized
INVISIBLE MARKINGS - 15mm	15 250 A <sup>15</sup>	TR 250 A <sub>3</sub> 15	X5 X5 250 A <sub>3</sub> 15		PZ 250 A <sup>15</sup>	•
INVISIBLE MARKINGS - 18mm	15 250 A <sub>18</sub>	TR 250 A <sup>18</sup>	X5 250 A <sub>3</sub> <sup>18</sup>		PZ 250 A <sub>3</sub> <sup>18</sup>	
INVISIBLE MARKINGS - Variable	15 250 A <sub>3</sub>	250 A <sub>3</sub>	X5 250 Å <sub>3</sub>		PZ 250 A <sub>3</sub>	

					<u> </u>	
			TREATMENT			COATING
SuperLite <sup>™</sup> 1.60	S Clear	Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-15.00 to +8.00	-15.00 to +8.00	-15.00 to +8.00		-15.00 to +8.00	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00		+0.75 to +4.00	
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	<b>S</b>
INVISIBLE MARKINGS - 11mm	250 A <sub>3</sub> <sup>11</sup>	T6 250 A <sub>3</sub> 11	X6 X9 250 A <sub>3</sub> 11		PZ6 250 A <sub>3</sub> 11	Clear, Transitions and
INVISIBLE MARKINGS - 13mm	250 A <sub>3</sub> <sup>16</sup>	T6 250 A <sub>3</sub> <sup>13</sup>	250 A <sub>3</sub> <sup>13</sup>		PZ6 250 A <sub>3</sub> <sup>13</sup>	Polarized
INVISIBLE MARKINGS - 15mm	16 250 A <sub>3</sub> <sup>15</sup>	T6 250 A <sup>15</sup>	X6 250 A <sub>3</sub> 15		PZ6 250 A <sub>3</sub> <sup>15</sup>	•
INVISIBLE MARKINGS - 18mm	16 250 A <sup>18</sup>	T6 250 A <sub>3</sub> <sup>18</sup>	X6 250 A <sub>3</sub> <sup>18</sup>		PZ6 250 A <sub>3</sub> <sup>18</sup>	
INVISIBLE MARKINGS - Variable	16 250 Å <sub>3</sub>	250 A <sub>3</sub>	250 A <sub>3</sub>		PZ6 250 A <sub>3</sub>	

	230 73	250 13	250 73		230 73	
			TREATMENT			COATING
SuperLite™ 1.67	S Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-16.75 to +9.00	-16.75 to +9.00	-16.75 to +9.00		-16.75 to +9.00	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00		+0.75 to +4.00	
CYLINDER	to -8.00	to -8.00	to -8.00		to -8.00	<b></b>
OTHER		Gray/Brown	Gray		Gray/Brown	Clear,
INVISIBLE MARKINGS - 11mm	57 250 A <sub>3</sub> 11	767 250 A <sub>3</sub> 11	X67 250 A <sub>3</sub> 11		PZ67 250 A <sub>3</sub> 11	Transiti@ns; XTRActive and
INVISIBLE MARKINGS - 13mm	67 250 A <sub>3</sub> <sup>13</sup>	767 250 A <sub>3</sub>	X67 250 A <sub>3</sub> <sup>13</sup>		PZ67 250 A <sub>3</sub> <sup>13</sup>	Polarized
INVISIBLE MARKINGS - 15mm	67 250 A <sup>15</sup>	T67 250 A <sub>3</sub> 15	X67 250 A <sub>3</sub> 15		PZ67 250 A <sub>3</sub> 15	•
INVISIBLE MARKINGS - 18mm	67 250 A\s	767 250 A <sub>3</sub> 18	X67 250 A <sub>18</sub>		PZ67 250 A <sub>18</sub>	
INVISIBLE MARKINGS - Variable	67 250 A <sub>3</sub>	T67 250 A <sub>3</sub>	X67 250 Å <sub>3</sub>		PZ67 250 A <sub>3</sub>	

			TREATMENT		COATING
SuperLite™1.74	8	Clear	Transiti@ns	S XTRActive	
POWER RANGE					
ADD POWER					
CYLINDER					
OTHER					
INVISIBLE MARKINGS - 11mm					
INVISIBLE MARKINGS - 13mm			COMING SOON		
INVISIBLE MARKINGS - 15mm					
INVISIBLE MARKINGS - 18mm					
INVISIBLE MARKINGS - Variable					

	TREATMENT				COATING	
DLC™/TRIVEX™	S Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-13.25 to +7.00	-13.25 to +7.00			-10.00 to +7.00	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00			+0.75 to +4.00	
CYLINDER	to -6.50	to -6.50			to -6.50	
OTHER		Gray/Brown			Gray/Brown/G-15	<b></b>
INVISIBLE MARKINGS - 11mm	250 A <sub>3</sub> 11	250 A <sub>3</sub> <sup>11</sup>			PTX 250 A <sub>3</sub> 11	Clear and Transiti@ns
INVISIBLE MARKINGS - 13mm	TX 250 A <sup>13</sup>	250 A <sub>3</sub> <sup>13</sup>			250 A <sub>3</sub> <sup>13</sup>	Trunside 113
INVISIBLE MARKINGS - 15mm	TX 250 A <sup>15</sup>	TTX 250 A <sup>15</sup>			PTX 250 A <sub>3</sub> <sup>15</sup>	•
INVISIBLE MARKINGS - 18mm	250 A <sub>3</sub> <sup>18</sup>	250 A <sub>18</sub>			PTX 250 A <sup>18</sup>	
INVISIBLE MARKINGS - Variable	TX 250 Å <sub>3</sub>	TTX 250 A <sub>3</sub>			PTX 250 A <sub>3</sub>	

	TREATMENT					COATING
POLYPLUS™/ POLYCARBONATE	Clear	S Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-14.75 to +8.00	-14.75 to +8.00	-14.75 to +8.00		-14.75 to +8.00	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00		+0.75 to +4.00	
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	<b></b>
OTHER		Gray/Brown	Gray		Gray/Brown/G-15	Clear,
INVISIBLE MARKINGS - 11mm	90 PC 250 A11	PT 250 A <sub>1</sub> 11	PX 250 A <sub>1</sub> 11		PPZ 250 A <sub>3</sub> 11	Transitions, XTRActive and
INVISIBLE MARKINGS - 13mm	90 PC 250 A <sup>13</sup>	PT (5) 250 A <sub>1</sub> 3	PX 250 A <sub>1</sub> 3		PPZ 250 A <sub>3</sub> <sup>13</sup>	Polarized
INVISIBLE MARKINGS - 15mm	PC 250 A <sup>15</sup>	PT 250 A <sup>15</sup>	PX 250 A <sub>15</sub>		PPZ 250 A <sup>15</sup>	•
INVISIBLE MARKINGS - 18mm	PC 250 A18	PT 250 A <sub>3</sub> 8	PX 250 A <sub>3</sub> <sup>18</sup>		PPZ 250 A <sup>18</sup>	
INVISIBLE MARKINGS - Variable	PC 250 Å <sub>3</sub>	97 PT 250 A <sub>3</sub>	PX 250 A <sub>3</sub>		PPZ 250 A <sub>3</sub>	

















## **EVERYDAY> PROGRESSIVE** Shamir Autograph III®

#### PRESCRIPTOR ORDER CODE:


AUTOGRAPH III 11 AUTOGRAPH III 18 AUTOGRAPH III 13 AUTOGRAPH III VARIABLE AUTOGRAPH III 15

#### PRODUCT FEATURES:

☐ CONVENTIONAL SV 💢 NATURAL POSTURE™

- Recommended min fitting heights are 11mm, 13mm, 15mm and 18mm
- Variable 11mm and up
- Prism to 4.00 Diopters

	TREAT	MENT	COATING
NXT	Photochromic	Polarized	
POWER RANGE	-1.50 to +7.00	-1.50 to +7.00	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00	
CYLINDER	to -6.50	to -6.50	
OTHER	Green/Copper	Gray/Brown	
INVISIBLE MARKINGS - 11mm	NXTP	NXTZ	
INVISIBLE MARKINGS - 13mm	NXTP 35 35 250 A <sup>3</sup> 3	NXTZ 39	
INVISIBLE MARKINGS - 15mm	NXTP	NXTZ	
INVISIBLE MARKINGS - 18mm	NXTP	NXTZ 30	
INVISIBLE MARKINGS - Variable	NXTP	NXTZ	













**AUTOGRAPH II 11 AUTOGRAPH II 15 AUTOGRAPH II 13 AUTOGRAPH II 18** 

#### PRODUCT FEATURES:

X FREEFORM PAL ☐ FREEFORM SV ☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

EYEPOINT TECHNOLOGY®
 AS-WORN TECHNOLOGY™

- Recommended min fitting heights are 11mm, 13mm, 15mm and 18mm
- Prism to 4.00 Diopters

7	lutograph	II

			TREATMENT			COATING
CR-39	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized	
POWER RANGE	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00	
CYLINDER	to -6.00	to -6.00	to -6.00	to -6.00	to -6.00	
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	•
INVISIBLE MARKINGS - 11mm	15 250 6911	TR 250 6911	X5	V5 250 6911	PZ 250 6911	
INVISIBLE MARKINGS - 13mm	15 250 6913	TR 250 6913	X5 X5 250 6913	V5 250 eə13	PZ 250 6913	
INVISIBLE MARKINGS - 15mm	15 250 6915	TR	X5	V5 V5 250 6915	PZ	
INVISIBLE MARKINGS - 18mm	15 250 eə18	TR	X5 X5 250 6918	V5 V5 250 ea18	PZ 250 6918	

	TREATMENT					COATING
SuperLite™ 1.60	S Clear	S Transiti@ns	<b>S</b> XTRActive	Vantage	Polarized	
POWER RANGE	-15.00 to +6.00	-15.00 to +6.00	-15.00 to +6.00		-15.00 to +6.00	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00		+0.75 to +4.00	
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	<u> </u>
INVISIBLE MARKINGS - 11mm	16 350 6911	T6 250 6911	X6 250 6911		PZ6 250 6911	
INVISIBLE MARKINGS - 13mm	16 250 6913	T6 250 eə13	X6 250 eə13		PZ6 250 6913	
INVISIBLE MARKINGS - 15mm	16	T6	X6 250 eə15		PZ6 <b>1</b> 250 6915	
INVISIBLE MARKINGS - 18mm	16 \$\mathbf{\sqrt}\$ \tag{\sqrt}\$ 250 \$\text{col}\$ 6018	T6 \$\mathcal{O}\$ \$\mathcal{O}\$ \$\mathcal{O}	X6 250 eə18		PZ6 250 6918	

			TREATMENT			COATING
SuperLite™ 1.67	S Clear	Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-16.00 to +8.25	-16.00 to +8.25	-16.00 to +8.25		-16.00 to +8.25	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00		+0.75 to +4.00	
CYLINDER	to -8.00	to -8.00	to -8.00		to -8.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS - 11mm	67 250 6911	T67 250 6911	X67 X67 250 6911		PZ67	
NVISIBLE MARKINGS 13mm	67 250 se13	T67 \$\mathcal{O}\$ \$\mathcal{O}\$ \$O	X67 250 6913		PZ67	
NVISIBLE MARKINGS 15mm	67 250 6915	T67 250 6915	X67 250 6915		PZ67 250 6915	
NVISIBLE MARKINGS 18mm	67 250 eə18	T67 250 eə18	X67 250 eə18		PZ67	

	TREATMENT		COATING
S Clear	Transiti@ns	XTRActive	
-16.00 to +12.00	-16.00 to +12.00	-16.00 to +12.00	
+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	
to -9.00	to -9.00	to -9.00	
	Gray/Brown	Gray	
74 50 250 6911	T74	X74	
74 55 250	T74	X74	
74 250 6915	174 17 250 6915	X74 X7 250 6915	
74 250 ea18	174 250 eə18	X74 250 eə18	
	-16.00 to +12.00 +0.75 to +3.50 to -9.00 74 250 eal1 250 eal3 74 250 eal5 74	Clear Transitions  -16.00 to +12.00	Clear Transitions XTRActive  -16.00 to +12.00

		TREATM	IENT		COATING
DLC™ TRIVEX™	S Clear	Transiti@ns	XTRActive	Polarized	
POWER RANGE	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00	
ADD POWER	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00	+0.75 to +4.00	
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50	
OTHER		Gray/Brown	Gray	Gray/Brown	
INVISIBLE MARKINGS - 11mm	TX 250 6911	7TX 250 6911	XX 250 6911	PTX 250 6911	
INVISIBLE MARKINGS - 13mm	TX 250 eə13	TTX 250 6913	XX 250 6913	PTX 250 6913	
INVISIBLE MARKINGS - 15mm	TX 250 6915	TTX 250 6915	XX 250 6915	PTX 250 6915	
INVISIBLE MARKINGS - 18mm	TX 250 eə18	7TX 250 ea18	XX 250 eə18	PTX	

		TREAT	MENT			COATING
POLYPLUS™/ POLYCARBONATE	S Clear	Transitions	XTRActive	Vantage	Polarized	
POWER RANGE	-14.75 to +6.50					
ADD POWER	+0.75 to +4.00					
CYLINDER	to -7.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS - 11mm	PC 250 6911	PT	PX 250 6911	PV 250 6911	PPZ	
INVISIBLE MARKINGS - 13mm	PC 250 6913	PT	PX 250 6913	PV 250 6913	PPZ 250 6913	
INVISIBLE MARKINGS - 15mm	PC 250 6915	PT 250 6915	PX 250 6915	PV 250 6915	PPZ 250 6915	
INVISIBLE MARKINGS - 18mm	PC 250 6918	250 se 18	PX 250 6918	PV 250 6918	PPZ 250 6918	

Denotes that material is available in a Shamir Freeform Blank™

Crizal AR Coating













## **EVERYDAY> PROGRESSIVE** Shamir **InTouch**™

PRESCRIPTOR ORDER CODE:

**INTOUCH 15** 

**INTOUCH 18** 

#### PRODUCT FEATURES:

☐ FREEFORM SV

☐ CONVENTIONAL SV

☐ AS-WORN TECHNOLOGY™ ☐ CONVENTIONAL PAL

EYEPOINT TECHNOLOGY®

			TREATMENT			COATING
CR-39	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	
CYLINDER	to -6.00	to -6.00	to -6.00	to -6.00	to -6.00	
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS - 15mm	15 30 250 115	TR	X5 250 115	V5 250 115	PZ 250 115	
INVISIBLE MARKINGS - 18mm	15 250 118	TR	X5 250 118	V5 250 118	PZ 250 118	

	TREATMENT	COATING
SuperLite™1.74	© Clear	
POWER RANGE	-18.75 to +15.50	
ADD POWER	+0.75 to +3.50	
CYLINDER	to -9.00	
OTHER		
INVISIBLE MARKINGS - 15mm	74 35 250 115	
INVISIBLE MARKINGS - 18mm	74 39 250 118	

			TREATMENT			COATING
SuperLite™ 1.60	Clear		<b>S</b> XTRActive	Vantage	Polarized	
POWER RANGE	-15.00 to +6.00	-15.00 to +6.00	-15.00 to +6.00		-15.00 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50		+0.75 to +3.50	
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS - 15mm	16 250 115	T6 250 115	X6 250 115		PZ6 250 I15	
INVISIBLE MARKINGS - 18mm	16 35 250 118	T6 250 118	X6 250 118		PZ6	

		TREATMENT						
DLC™ TRIVEX™	© Clear	Transiti@ns	XTRActive	Polarized				
POWER RANGE	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00				
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50				
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50				
OTHER		Gray/Brown		Gray/Brown				
INVISIBLE MARKINGS - 15mm	TX	TTX 250 115	XX 250 115	PTX 250 115				
INVISIBLE MARKINGS - 18mm	TX 250 118	TTX 250 118	<b>3</b>	PTX 250 118				

	TREATMENT					
SuperLite™ 1.67	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-16.00 to +8.00	-16.00 to +8.00	-16.00 to +8.00		-16.00 to +8.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50		+0.75 to +3.50	
CYLINDER	to -8.00	to -8.00	to -8.00		to -8.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS - 15mm	250 I15	T67 250 115	X67 X67 250   115		PZ67	
INVISIBLE MARKINGS - 18mm	250 I18	T67 250 118	X67 250 118		PZ67	

		TREAT	MENT			COATING
POLYPLUS™/ POLYCARBONATE	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-14.75 to +6.00					
ADD POWER	+0.75 to +3.50					
CYLINDER	to -7.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS - 15mm	PC 250 I15	PT	PX 250 I15	PV 250 I15	PPZ 250 115	
INVISIBLE MARKINGS - 18mm	PC 250 118	PT 250 118	PX 250 118	PV 250 118	PPZ 250 118	



















spectrum\*

**SPECTRUM 18** 

PRESCRIPTOR ORDER CODE:

**SPECTRUM 14** 

**SPECTRUM 16** 

#### PRODUCT FEATURES:

☐ FREEFORM SV ☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

**▲ EYEPOINT TECHNOLOGY®** ☐ AS-WORN TECHNOLOGY™

## NOTE:

- Recommended min fitting heights are 14mm, 16mm and 18mm
- Prism to 4.00 Diopters

			TREATMENT			COATING
CR-39	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-12.25 to +6.00					
ADD POWER	+0.75 to +3.50					
CYLINDER	to -6.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	•
INVISIBLE MARKINGS - 14mm	15 250 SP14	TR 250 SP14	X5 250 SP14	V5 250 SP14	PZ 250 SP14	
INVISIBLE MARKINGS - 16mm	15 250 SP16	TR 250 SP16	X5 250 SP16	V5 250 SP16	PZ	
INVISIBLE MARKINGS - 18mm	15 250 SP18	TR 250 SP18	X5 250 SP18	V5 250 SP18	PZ 250 SP18	

		TREATMENT						
SuperLite™1.74	Clear	Transiti@ns	S XTRActive					
POWER RANGE	-16.00 to +11.50	-16.00 to +11.50	-16.00 to +11.50					
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50					
CYLINDER	to -9.00	to -9.00	to -9.00					
OTHER		Gray/Brown	Gray	<b>—</b>				
INVISIBLE MARKINGS - 14mm	74	174 250 SP14	X74 250 SP14					
INVISIBLE MARKINGS - 16mm	74 55 250 SP16	174 250 SP16	X74 250 SP16					
INVISIBLE MARKINGS - 18mm	74 250 SP18	174 250 SP18	X74 X7 X7 250 SP18					

			TREATMENT			COATING
SuperLite™ 1.60	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-15.00 to +6.00	-15.00 to +6.00	-15.00 to +6.00		-15.00 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50		+0.75 to +3.50	
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	<u></u>
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS - 14mm	16 250 SP14	T6 250 SP14	X6 250 SP14		PZ6	
INVISIBLE MARKINGS - 16mm	16 550 SP16	76 250 SP16	X6 250 SP16		PZ6	
INVISIBLE MARKINGS - 18mm	16 250 SP18	76 250 SP18	X6 250 SP18		PZ6 250 SP18	

		TREATM	IENT		COATING
DLC™ TRIVEX™	S Clear	Transiti@ns XTRActive		Polarized	
POWER RANGE	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50	
OTHER		Gray/Brown	Gray	Gray/Brown	
INVISIBLE MARKINGS - 14mm	TX 250 SP14	TTX 250 SP14	XX 250 SP14	PTX 250 SP14	•
INVISIBLE MARKINGS - 16mm	TX 250 SP16	TTX 250 SP16	250 SP16	PTX 250 SP16	
INVISIBLE MARKINGS - 18mm	TX 250 SP18	TTX	250 SP18	PTX 250 SP18	

			TREATMENT			COATING
SuperLite™ 1.67	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-16.00 to +8.00	-16.00 to +8.00	-16.00 to +8.00		-16.00 to +8.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50		+0.75 to +3.50	
CYLINDER	to -8.00	to -8.00	to -8.00		to -8.00	
OTHER		Gray/Brown	Gray		Gray/Brown	<b>(</b>
INVISIBLE MARKINGS - 14mm	67 250 SP14	T67 250 SP14	X67 250 SP14		PZ67 250 SP14	
INVISIBLE MARKINGS - 16mm	67 250 SP16	T67 250 SP16	X67 250 SP16		PZ67 250 SP16	
INVISIBLE MARKINGS - 18mm	67 250 SP18	T67	X67 X9 250 SP18		PZ67	

			MENT			COATING
POLYPLUS™/ POLYCARBONATE	S Clear	S Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-14.75 to +6.00					
ADD POWER	+0.75 to +3.50					
CYLINDER	to -7.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS - 14mm	PC 250 SP14	PT	PX 250 SP14	PV 250 SP14	PPZ 250 SP14	
INVISIBLE MARKINGS - 16mm	PC 250 SP16	PT 250 SP16	PX 250 SP16	PV 250 SP16	PPZ 250 SP16	
INVISIBLE MARKINGS - 18mm	PC 250 SP18	PT	PX 250 SP18	PV 250 SP18	PPZ	

Crizal AR Coating





Zeiss AR Coating











element

**ELEMENT 16** 

**ELEMENT 19** 

PRESCRIPTOR ORDER CODE:

#### PRODUCT FEATURES:

☐ FREEFORM SV ☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

EYEPOINT TECHNOLOGY®
 AS-WORN TECHNOLOGY™

- Recommended min fitting height is 16mm and 19 mm
- Prism to 4.00 Diopters

			TREATMENT			COATING
CR-39	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized	
POWER RANGE	-7.00 to +4.00	-7.00 to +4.00	-7.00 to +4.00		-7.00 to +4.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50		+0.75 to +3.50	
CYLINDER	to -6.00	to -6.00	to -6.00		to -6.00	
OTHER		Gray/Brown	Gray		Gray/Brown/G-15	
INVISIBLE MARKINGS - 16mm	15 250 ES	TR TR 250 ES	X5 250 ES		PZ	
INVISIBLE MARKINGS - 19mm	15 250 E	TR	X5 250 E		PZ	

	TREATMENT	COATING
SuperLite™ 1.74		
POWER RANGE		
ADD POWER		
CYLINDER		
OTHER	-	
INVISIBLE MARKINGS - 16mm	-	
INVISIBLE MARKINGS - 19mm	-	

	TREATMENT					COATING
SuperLite™ 1.60	S Clear	Transiti@ns	<b>S</b> XTRActive	Vantage	Polarized	
POWER RANGE	-10.00 to +6.00	-10.00 to +6.00	-10.00 to +6.00			
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50			
CYLINDER	to -7.00	to -7.00	to -7.00			
OTHER		Gray/Brown	Gray			
INVISIBLE MARKINGS - 16mm	16 250 ES	76 250 ES	X6 250 ES			
INVISIBLE MARKINGS - 19mm	16 5 250 E	76 7 250 E	X6 250 E			

	TREATMENT						
DLC™ TRIVEX™	DLC™ TRIVEX™ Clear		XTRActive	Polarized			
POWER RANGE	-13.25 to +6.00	-13.25 to +6.00	-13.25 to +6.00				
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50				
CYLINDER	to -6.50	to -6.50	to -6.50				
OTHER		Gray/Brown	Gray				
INVISIBLE MARKINGS - 16mm	TX 250 ES	TTX TO 250 ES	XX 250 ES				
INVISIBLE MARKINGS - 19mm	TX 250 E	1TIX 250 E	250 E				

			TREATMENT			COATING
SuperLite™ 1.67	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-12.50 to +8.00	-12.50 to +8.00	-12.50 to +8.00			
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50			
CYLINDER	to -8.00	to -8.00	to -8.00			
OTHER		Gray/Brown	Gray			
INVISIBLE MARKINGS - 16mm	67 250 ES	T67 250 ES	X67 250 ES			
INVISIBLE MARKINGS - 19mm	€ 67 250 E	T67 250 E	X67 250 E			

DOLLAR THE		TREAT	MENT			COATING
POLYPLUS™/ POLYCARBONATE	Clear	Transitions	XTRActive	Vantage	Polarized	
POWER RANGE	-10.00 to +6.00	-10.00 to +6.00	-10.00 to +6.00		-10.00 to +6.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50		+0.75 to +3.50	
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown/G-15	
INVISIBLE MARKINGS - 16mm	PC 250 ES	<b>1</b> PT <b>1 1 1 2 5 0 1 1 1 1 1 1 1 1 1 1</b>	PX 250 ES		PPZ 250 ES	
INVISIBLE MARKINGS - 19mm	<b>⊕</b> PC 250 E	97 250 E	PX 250 E		PPZ 250 E	















FIRST PAL

PRESCRIPTOR ORDER CODE:

FIRSTPAL 15

☐ FREEFORM SV ☐ CONVENTIONAL PAL

☐ CONVENTIONAL SV

**▲ EYEPOINT TECHNOLOGY®** ☐ AS-WORN TECHNOLOGY™

PRODUCT FEATURES:

	TREATMENT					
CR-39	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized	
POWER RANGE	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	
ADD POWER	+0.75 to +1.50	+0.75 to +1.50	+0.75 to +1.50	+0.75 to +1.50	+0.75 to +1.50	
CYLINDER	to -6.00	to -6.00	to -6.00	to -6.00	to -6.00	
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS	15 150 FP	TR 150 FP	X5 150 FP	V5 150 FP	PZ 150 FP	

		TREATMENT		COATING
SuperLite <sup>™</sup> 1.74	S Clear	S Transiti@ns	S XTRActive	
TOTAL NEAR POWER RANGE				
DYNAMIC REDUCTION				
CYLINDER				
OTHER				
INVISIBLE MARKINGS				

SuperLite™ 1.60	TREATMENT						
	S Clear	Transiti@ns	<b>S</b> XTRActive	Vantage	Polarized		
POWER RANGE	-15.00 to +6.00	-15.00 to +6.00	-15.00 to +6.00		-15.00 to +6.00		
ADD POWER	+0.75 to +1.50	+0.75 to +1.50	+0.75 to +1.50		+0.75 to +1.50		
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00		
OTHER		Gray/Brown	Gray		Gray/Brown	•	
INVISIBLE MARKINGS	16 150 FP	150 FP	150 FP		150 FP		

DLC™ TRIVEX™	TREATMENT					
	Clear	Transiti@ns <sup>-</sup>	XTRActive	XTRActive		
TOTAL NEAR POWER RANGE						
DYNAMIC REDUCTION						
CYLINDER						
OTHER						
INVISIBLE MARKINGS						

SuperLite™ 1.67	TREATMENT						
	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized		
TOTAL NEAR POWER RANGE							
DYNAMIC REDUCTION							
CYLINDER							
OTHER							
INVISIBLE MARKINGS							

70.00		TREAT	MENT			COATING
POLYPLUS™/ POLYCARBONATE	S Clear	S Transitions	XTRActive	Vantage	Polarized	
POWER RANGE	-14.75 to +6.00					
ADD POWER	+0.75 to +1.50					
CYLINDER	to -7.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS	PC	PT	PX	PV 150 FP	PPZ	


















CR-39	TREATMENT						
	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized		
POWER RANGE	-8.50 to +6.75	-8.50 to +6.75					
ADD POWER	+0.75 to +3.50	+0.75 to +3.50			-		
NOMINAL BASE CURVE	2, 3, 4.5, 5.5, 6.5, 7.5	2, 3, 4.5, 5.5, 6.5, 7.5					
OTHER/COATING	Hard Coated/Uncoated	Gray/Brown					
INVISIBLE MARKINGS	○ ○ <b>⑤</b> 250	○ ○ <b>⑤</b> 250					

SuperLite™ 1.60	TREATMENT						
	Clear	Transiti@ns	XTRActive	Vantage	Polarized		
POWER RANGE	-12.00 to +8.00	-12.00 to +8.00					
ADD POWER	+1.00 to +3.50	+1.00 to +3.50					
NOMINAL BASE CURVE	1.75, 3, 4.5, 5.5, 6.5, 7.5	1.75, 3, 4.5, 5.5, 6.5, 7.5					
OTHER/COATING	Hard Coated/Uncoated	Gray					
INVISIBLE MARKINGS	○ ○ <b>⑤</b> H 250	○ ○ <b>⑤</b> H 250					

SuperLite™ 1.67	TREATMENT						
	Clear	Transiti@ns	XTRActive	Vantage	Polarized		
POWER RANGE	-12.50 to +8.00	-12.50 to +8.00			-12.50 to +8.00		
ADD POWER	+1.00 to +3.50	+1.00 to +3.50			+1.00 to +3.50		
NOMINAL BASE CURVE	1.5, 3, 4.5, 5.5, 6.5, 7.5	1.5, 3, 4.5, 5.5, 6.5, 7.5			1.5, 3, 4.5, 5.5, 6.5, 7.5		
OTHER/COATING	Hard Coated/Uncoated	Gray			<b>⊚ ⊚</b> Gray		
INVISIBLE MARKINGS	○ ○ � 67 250	○ ○ <b>⑤</b> 67 250			O O		

#### PRODUCT FEATURES:

☐ FREEFORM PAL ☐ FREEFORM SV CONVENTIONAL PAL **∠** EYEPOINT TECHNOLOGY® ☐ AS-WORN TECHNOLOGY®

## NOTE:

- Recommended min fitting height is 19mm
- Cylinder to -6.00
- Prism to 4.00 Diopters

SuperLite™1.74	TREATMENT
POWER RANGE	
ADD POWER	
NOMINAL BASE CURVE	
OTHER/COATING	
INVISIBLE MARKINGS	

DLC™ TRIVEX™	TREATMENT						
	Clear	Transiti@ns	XTRActive	Polarized			
POWER RANGE							
ADD POWER							
NOMINAL BASE CURVE							
OTHER/COATING							
INVISIBLE MARKINGS							

POLYPLUS™/ POLYCARBONATE		TREATMENT					
	Clear	Transiti <b>©</b> ns	XTRActive	Vantage	Polarized		
POWER RANGE	-12.00 to +7.50	-12.00 to +7.50					
ADD POWER	+1.00 to +3.50	+1.00 to +3.50					
NOMINAL BASE CURVE	1.75, 3, 4.5, 5.5, 6.5, 7.5	1.75, 3, 4.5, 5.5, 6.5, 7.5					
OTHER/COATING	Hard Coated:	Gray					
INVISIBLE MARKINGS	O O P 250	O O P 250					






Zeiss AR Coating



iCoat AR Coating





CR-39	TREATMENT						
	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized		
POWER RANGE	-8.50 to +6.00	-8.50 to +6.00					
ADD POWER	+0.75 to +3.50	+0.75 to +3.50					
BASE CURVE	1.5, 3, 5, 6.5, 7.5	1.5, 3, 5, 6.5, 7.5					
OTHER/COATING	Hard Coated/Uncoated	Gray					
INVISIBLE MARKINGS	<b>♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦</b>	<b>♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦</b>					

SuperLite™ 1.60	TREATMENT						
	Clear	Transiti@ns	XTRActive	Vantage	Polarized		
POWER RANGE	-11.25 to +7.00	-11.25 to +7.00					
ADD POWER	+0.75 to +3.50	+1.00 to +3.50					
BASE CURVE	1.5, 3, 5, 6.5, 7.5	1.5, 3, 5, 6.5, 7.5					
OTHER/COATING	Hard Coated/Uncoated	Gray					
INVISIBLE MARKINGS	<b>○ ○ ○ ○ ○ ○ ○ ○ ○ ○</b>	<b>♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦</b>					

			TREATMENT		
SuperLite™ 1.67	Clear	Transiti@ns	XTRActive	Vantage	Polarized
POWER RANGE	-12.50 to +6.00	-12.50 to +6.00			
ADD POWER	+1.00 to +3.00	+1.00 to +3.00			
BASE CURVE	1.5, 3, 4.5, 5.75, 7	1.5, 3, 4.5, 5.75, 7			
OTHER/COATING	Hard Coated/Uncoated	Gray			
INVISIBLE MARKINGS	<b>○ ○ ○ ○ ○ ○ ○ ○ ○ ○</b>	<b>○ ○ ○ ○ ○ ○ ○ ○ ○ ○</b>			

#### PRODUCT FEATURES:

☐ FREEFORM PAL ☐ FREEFORM SV CONVENTIONAL PAL **∠** EYEPOINT TECHNOLOGY® ☐ AS-WORN TECHNOLOGY®

- Recommended min fitting height is 16mm
- Cylinder to -6.00
- Prism to 4.00 Diopters

	TREATMENT
SuperLite™1.74	Clear
POWER RANGE	
ADD POWER	
NOMINAL BASE CURVE	
OTHER/COATING	
INVISIBLE MARKINGS	

		TREATM	IENT	
DLC™ TRIVEX™	Clear	Transiti@ns	XTRActive	Polarized
POWER RANGE				
ADD POWER				
NOMINAL BASE CURVE				
OTHER/COATING				
INVISIBLE MARKINGS				

		TREATMENT		TREATMENT			
POLYPLUS™/ POLYCARBONATE	Clear	Transiti@ns	XTRActive	Vantage	Polarized		
POWER RANGE	-8.50 to +6.00	-8.50 to +6.00					
ADD POWER	+1.00 to +3.00	+1.00 to +3.00					
BASE CURVE	1.5, 3, 5, 7.5	1.5, 3, 5, 7.5					
OTHER/COATING	Hard Coated:	Gray					
INVISIBLE MARKINGS	O O P 250	O O P 250					

	TREATMENT					
Glass	Clear	Photo				
POWER RANGE	-5.25 to +6.00	-5.25 to +6.00				
ADD POWER	+0.75 to +3.50	+0.75 to +3.50				
BASE CURVE	3, 5, 7.5	3, 5, 7.5				
OTHER/COATING	<b>⊌ ⊌</b>	<b>◎ ◎</b> Thin & Dark				
INVISIBLE MARKINGS	<b>○</b>	TD				













		TREATMENT			
CR-39	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized
POWER RANGE	-8.50 to +5.75	-8.50 to +5.75			-5.75 to +6.00
ADD POWER	+0.75 to +3.50	+0.75 to +3.50			+1.00 to +3.00
BASE CURVE	1.5, 3, 5, 6.5, 7.5	1.5, 3, 5, 6.5, 7.5			3, 5, 7.5
OTHER/COATING	Hard Coated/Uncoated	Gray			Gray/Brown
INVISIBLE MARKINGS	<b>⊕ ⊕</b>	<b>⊕ ⊕</b>			PZ 250

		TREATMENT			
SuperLite™ 1.60	Clear	Transiti@ns	XTRActive	Vantage	Polarized
POWER RANGE	-11.25 to +7.00	-11.25 to +7.00			
ADD POWER	+0.75 to +3.50	+1.00 to +3.50			
BASE CURVE	1.5, 3, 5, 6.5, 7.5	1.5, 3, 5, 7.5			
OTHER/COATING	Hard Coated/Uncoated	Gray			
INVISIBLE MARKINGS					

		TREATMENT			
SuperLite™ 1.67	Clear	Transiti@ns	XTRActive	Vantage	Polarized
POWER RANGE	-12.50 to +7.50				
ADD POWER	+1.00 to +3.50				
BASE CURVE	1.5, 3, 5, 7.5				
OTHER/COATING	Hard Coated/Uncoated				
INVISIBLE MARKINGS					

#### PRODUCT FEATURES:

☐ FREEFORM PAL ☐ FREEFORM SV CONVENTIONAL PAL **∠** EYEPOINT TECHNOLOGY® ☐ AS-WORN TECHNOLOGY®

## NOTE:

- Recommended min fitting height is 16mm
- Cylinder to -6.00
- Prism to 4.00 Diopters

	TREATMENT
SuperLite™1.74	
POWER RANGE	
ADD POWER	
BASE CURVE	
OTHER/COATING	
INVISIBLE MARKINGS	

	TREATMENT					
DLC™ TRIVEX™	Clear	Transiti@ns	XTRActive	Polarized		
POWER RANGE	-5.75 to +6.00					
ADD POWER	+1.00 to +3.00					
BASE CURVE	3, 5, 7.5					
OTHER/COATING	<b>├ ├ ├ ├ ├ ├</b> Hard Coated/Uncoated					
INVISIBLE MARKINGS	₩ ₩ TX 250					

		TREAT	MENT		
POLYPLUS™/ POLYCARBONATE	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized
POWER RANGE	-12.00 to +7.50				
ADD POWER	+1.00 to +3.00				
BASE CURVE	1.5, 3, 5, 7				
OTHER/COATING	PolyPlus <sup>TM*</sup> - HC				
INVISIBLE MARKINGS	O O P 250				

	TREATMENT					
Glass	Clear	Photo				
POWER RANGE	-9.00 to +6.00	-9.00 to +6.00				
ADD POWER	+0.75 to +3.50	+0.75 to +3.50				
BASE CURVE	1.5, 3, 5, 7	1.5, 3, 5, 7				
OTHER/COATING	© Clear	<b>◯ ◯ ◯ ◯ Gray Extra</b>				
INVISIBLE MARKINGS	<b>☞ ☞</b> 16 250	<b>☞ ☞</b> 16 250				









iCoat AR Coating

AUTOGRAPH II SV AW

PRESCRIPTOR ORDER CODE:

☐ FREEFORM PAL 

☐ CONVENTIONAL SV

**▲ EYEPOINT TECHNOLOGY®** ☐ AS-WORN TECHNOLOGY™

PRODUCT FEATURES:

NOTE:

• Prism to 4.00 Diopters

# Autograph II SINGLE VISION™

		HGEE VIOLON						
		TREATMENT						
CR-39	Clear	Transiti@ns	XTRActive	Vantage	Polarized			
POWER RANGE	-14.00 to +8.00							
ADD POWER								
CYLINDER	to -6.00							
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15			
INVISIBLE MARKINGS	15 FF SV**	TR SV*	X5 FF SV*	V5 FF SV**	PZ FF SV**			

		TREATMENT					
SuperLite™1.74	S Clear	S Transiti@ns	S XTRActive				
POWER RANGE	-16.00 to +12.50	-16.00 to +12.50	-16.00 to +12.50				
ADD POWER							
CYLINDER	to -9.00	to -9.00	to -9.00				
OTHER		Gray/Brown	Gray				
INVISIBLE MARKINGS	74 O O FF SV*	T74  OFF  FF  SV*	X74 OFF FF SV**				

		TREATMENT				COATING
SuperLite™ 1.60	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-14.00 to +8.00	-14.00 to +8.00	-14.00 to +8.00		-14.00 to +8.00	
ADD POWER						
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS	16 FF SV*	T6 FF SV*	X6 FF SV		PZ6 FF SV*	

		TREATMENT					
DLC™ TRIVEX™	S Clear	Transiti@ns	XTRActive	Polarized			
POWER RANGE	-14.00 to +7.50	-14.00 to +7.50	-14.00 to +7.50	-14.00 to +7.50			
ADD POWER							
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50			
OTHER		Gray/Brown	Gray	Gray/Brown			
INVISIBLE MARKINGS	TX FF SV*	TTX FF SV*	XX FF SV*	PTX FF SV			

		TREATMENT				COATING
SuperLite™ 1.67	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-16.00 to +16.00	-16.00 to +16.00	-16.00 to +16.00		-16.00 to +16.00	
ADD POWER						
CYLINDER	to -8.00	to -8.00	to -8.00		to -8.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS	67 FF SV	T67	X67 FF SV*		PZ67	

		TREAT	TREATMENT			COATING
POLYPLUS™/ POLYCARBONATE	S Clear	S Transitions	XTRActive	Vantage	Polarized	
POWER RANGE	-14.00 to +8.75					
ADD POWER						
CYLINDER	to -7.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS	PC FF SV*	PT FF SV*	PX FF SV*	PV FF SV**	PPZ FF SV**	















AU2-SIV-GUI-REF-092712

SPECTRUM SV

★ FREEFORM SV

☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

#### PRODUCT FEATURES: ☐ FREEFORM PAL

**▲ EYEPOINT TECHNOLOGY®** ☐ AS-WORN TECHNOLOGY™

## NOTE:

• Prism to 4.00 Diopters



	TREATMENT					
CR-39	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-14.00 to +8.00					
ADD POWER						
CYLINDER	to -6.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS	15 FF SV	TR SV	X5 FF SV	V5 FF SV	PZ FF SV	

		TREATMENT		COATING
SuperLite <sup>™</sup> 1.74	S Clear	S Transiti@ns	S XTRActive	
POWER RANGE	-16.00 to +12.50	-16.00 to +12.50	-16.00 to +12.50	
ADD POWER				
CYLINDER	to -9.00	to -9.00	to -9.00	
OTHER		Gray/Brown	Gray	
INVISIBLE MARKINGS	74 FF SV	T74  OFF SV	X74 FF SV	

		TREATMENT				
SuperLite™ 1.60	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-14.00 to +8.00	-14.00 to +8.00	-14.00 to +8.00		-14.00 to +8.00	
ADD POWER						
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS	16 FF SV	T6 FF SV	X6 FF SV		PZ6 FF SV	

		TREATMENT					
DLC™ TRIVEX™	6 Clear	Transiti@ns	XTRActive	Polarized			
POWER RANGE	-14.00 to +7.50	-14.00 to +7.50	-14.00 to +7.50	-14.00 to +7.50			
ADD POWER							
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50			
OTHER		Gray/Brown	Gray	Gray/Brown			
INVISIBLE MARKINGS	TX FF SV	TTX FF SV	XX FF SV	PTX FF SV			

			TREATMENT			COATING
SuperLite™ 1.67	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-16.00 to +16.00	-16.00 to +16.00	-16.00 to +16.00		-16.00 to +16.00	
ADD POWER						
CYLINDER	to -8.00	to -8.00	to -8.00		to -8.00	
OTHER		Gray/Brown	Gray		Gray/Brown	•
INVISIBLE MARKINGS	67 FF SV	T67 FF SV	X67 FF SV		PZ67 FF SV	


		TREATMENT				COATING
POLYPLUS™/ POLYCARBONATE	S Clear	S Transitions	XTRActive	Vantage	Polarized	
POWER RANGE	-14.00 to +8.75					
ADD POWER						
CYLINDER	to -7.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	•
INVISIBLE MARKINGS	PC FF SV	PT FF SV	PX FF SV	PV FF SV	PPZ FF SV	













## **EVERYDAY> SINGLE VISION**

# Single Vision

			TREATMENT		
CR-39	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized
POWER RANGE	-10.00 to +6.00	-11.00 to +6.00			-8.00 to +6.00
ADD POWER					
CYLINDER	to -6.00	to -6.00			to -4.00
BASE CURVE	2, 3.50, 4.25, 6.25, 7.25	.5, 2.25, 4.25, 5.25, 6.25, 8.25			2.25, 3.25, 4.25, 5.25, 6.25, 7.25, 8.25
	Wrap: 4, 6, 7, 8				
OTHER/COATING	Hard Coated/Uncoated	Gray			Gray/Brown
INVISIBLE MARKINGS					

SuperLite™ 1.60	TREATMENT						
	Clear	⑤ Transiti⊚ns	<b>S</b> XTRActive	Vantage	Polarized		
POWER RANGE	-15.00 to +9.00	-15.00 to +9.00	-15.00 to +9.00		-9.50 to +7.00		
ADD POWER							
CYLINDER	to -7.00	to -7.00	to -7.00		to -4.00		
BASE CURVE	.5, 2, 3, 4, 5, 6, 7, 8, 9	.5, 2, 3, 4,	.5, 2, 3, 4, 5, 6, 7, 8, 9		1.50, 2, 3, 4, 5,		
	Wrap: 6, 7, 8	5, 6, 7, 8, 9	5, 6, 7, 8, 9		6, 7, 8, 9,		
OTHER /COATING	Hard Coated/Uncoated	Gray/Brown	Gray		Gray/Brown		
INVISIBLE MARKINGS							

	TREATMENT						
SuperLite™ 1.67	Clear	Transiti@ns	XTRActive	Vantage	Polarized		
POWER RANGE	-16.00 to +16.25	-16.00 to +16.25	-16.00 to +16.25		-12.00 to +7.00		
ADD POWER							
CYLINDER	to -8.00	to -8.00	to -8.00		to -4.00		
BASE CURVE	.5, 2, 3, 4, 5, 6, 7, 8, 9, 11, 12.5	.5, 2, 3, 4, 5, 6,	.5, 2, 3, 4, 5, 6, 7, 8, 9, 11, 12.5		1.25, 2.75, 3.75, 4.75, 5.25,		
	Wrap: 6,7,8	7, 8, 9, 11, 12.5	Wrap: 6,7,8		6.75, 8		
OTHER /COATING	Hard Coated/Uncoated	Gray/Brown	Gray		Gray/Brown		
INVISIBLE MARKINGS							

	Crizal AR Coating	Hoya A
$\overline{}$	•	

AR Coating







## iCoat AR Coating

#### PRODUCT FEATURES:

☐ FREEFORM PAL ☐ FREEFORM SV ☐ CONVENTIONAL PAL CONVENTIONAL SV

☐ EYEPOINT TECHNOLOGY® ☐ AS-WORN TECHNOLOGY®

SuperLite™1.74	TREATMENT
POWER RANGE	-18.00 to +8.50
ADD POWER	
CYLINDER	to -9.00
NOMINAL BASE	.5, 1, 2, 3, 4, 5, 6, 7, 8, 9
CURVE	Extra Thick: .5, 1, 2
OTHER/COATING	Hard Coated/Uncoated
INVISIBLE MARKINGS	

	TREATMENT							
DLC™ TRIVEX™	Clear	⑥ Transiti@ns <sup>-</sup>	XTRActive	Polarized				
POWER RANGE	-14.00 to +7.50	-14.00 to +7.50		-7.00 to +7.50				
ADD POWER								
CYLINDER	to -6.50	to -6.50		to -4.00				
NOMINAL BASE CURVE	.5, 1, 2, 3, 4, 5, 6, 7, 8, 9 DLC™ Trivex™	.5, 1, 2, 3, 4, 5, 6, 7, 8, 9		2.25, 4.25, 6.25, 8.25				
CURVE	Wrap: 6.25, 7.25, 8.25			6.25, 8.25				
OTHER/COATING	Hard Coated/Uncoated	Gray/Brown		Gray/Brown				
INVISIBLE MARKINGS								

POLYPLUS™/ POLYCARBONATE					
	Clear	Transitions	XTRActive	Vantage	Polarized
POWER RANGE	-14.75 to +9.00	-14.75 to +9.00	-14.75 to +9.00		-10.00 to +6.00
ADD POWER					
CYLINDER	to -7.00	to -7.00	to -7.00		to -4.00
BASE CURVE	.5, 2, 3, 4, 5.25, 6.25, 7.5, 8.5, 9.5	.5, 2, 3, 4, 5.25, 6.25, 7.5, 8.5, 9.5	.5, 2, 3, 4, 5.25, 6.25, 7.5, 8.5, 9.5		1.50, 2.25, 3.25, 4.25, 5.50, 6.50, 7.50, 8.50
OTHER/COATING	Hard Coated:	Gray/Brown	Gray		Gray/Brown
INVISIBLE MARKINGS					

## **EVERYDAY> SINGLE VISION**

# Single Vision

NXT®	TREATMENT					
	Photochromic	Polarized				
POWER RANGE	-5.00 to +4.00	-5.00 to +4.00				
ADD POWER						
CYLINDER	to -6.00	to -4.00				
BASE CURVE	6.00, 8.00	6.00, 8.00				
OTHER/COATING	Green/Copper	Gray/Brown				
INVISIBLE MARKINGS						

#### PRODUCT FEATURES:

☐ FREEFORM PAL ☐ FREEFORM SV ☐ CONVENTIONAL PAL CONVENTIONAL SV

☐ EYEPOINT TECHNOLOGY® ☐ AS-WORN TECHNOLOGY®











## **PERFORMANCE> SPORT**

PRESCRIPTOR ORDER CODE:

GOLF 19

#### PRODUCT FEATURES:

☐ FREEFORM SV ☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

EYEPOINT TECHNOLOGY®
 AS-WORN TECHNOLOGY™

- Recommended min fitting height is 19mm
- Prism to 4.00 Diopters

		COATING				
CR-39	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized	
POWER RANGE			-			
ADD POWER						
CYLINDER	-	-	-	-		
OTHER						
INVISIBLE MARKINGS					-	

SuperLite™1.74	TREATMENT				
	© Clear				
POWER RANGE					
ADD POWER					
CYLINDER					
OTHER					
INVISIBLE MARKINGS	-				

	TREATMENT					
SuperLite™ 1.60	S Clear	S Transiti@ns	<b>S</b> XTRActive	Vantage	Polarized	
POWER RANGE	-6.00 to +5.25	-6.00 to +5.25	-6.00 to +5.25		-6.00 to +5.25	
ADD POWER	+1.00 to +3.50	+1.00 to +3.50	+1.00 to +3.50		+1.00 to +3.50	
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS	350 \( \frac{16}{\text{V}} \)	350 T6	350 X6		PZ6 350 V	

	TREATMENT					
DLC™ TRIVEX™	S Clear	lear STransiti@ns		Polarized		
POWER RANGE	-5.00 to +4.00	-5.00 to +4.00	-5.00 to +4.00 -5.00 to +4.00		<u></u>	
ADD POWER	+1.00 to +3.50	+1.00 to +3.50	+1.00 to +3.50	+1.00 to +3.50		
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50		
OTHER		Gray/Brown	Gray	Gray/Brown		
INVISIBLE MARKINGS	<b>1</b> X <b>3</b> 50	350	350 XX	97X 350 V		

			COATING			
SuperLite <sup>™</sup> 1.67	Clear	Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE						
ADD POWER						
CYLINDER						
OTHER						
INVISIBLE MARKINGS		-	-			

		TREAT	MENT		COATING	
POLYPLUS™/ POLYCARBONATE	Clear	Transiti@ns XTRActive		Vantage Polarized		
POWER RANGE	-6.00 to +5.25	-6.00 to +5.25	-6.00 to +5.25	-6.00 to +5.25	-6.00 to +5.25	
ADD POWER	+1.00 to +3.50	+1.00 to +3.50	+1.00 to +3.50	+1.00 to +3.50	+1.00 to +3.50	
CYLINDER	to -7.00	to -7.00	to -7.00	to -7.00	to -7.00	
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS	350 PC	350 PT €	350 PX	350 PV	350 PPZ	















**AUTOGRAPH II ATTITUDE 15 AUTOGRAPH II ATTITUDE 18** 

#### PRODUCT FEATURES:

☐ FREEFORM SV ☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

AS-WORN TECHNOLOGY™

#### NOTE:

- Recommended min fitting heights are 15mm and 18mm
- Prism to 4.00 Diopters

				COATING		
CR-39	Clear	Transiti@ns XTRActive		Vantage	Polarized	
POWER RANGE	-5.00 to +4.00 -5.00 to +4.00		-5.00 to +4.00 -5.00 to +4.00		-5.00 to +4.00	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	
CYLINDER	to -6.00	to -6.00	to -6.00	to -6.00	to -6.00	
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS - 15mm	15 250 FF-AS	TR	X5 250 FF-AS	V5 250 FF-AS	PZ SD FF-AS	
INVISIBLE MARKINGS - 18mm	15 250 FFA	TR 250 FFA	X5 250 FFA	V5 250 FFA	PZ S 250 FFA	

	TREATMENT	COATING
SuperLite™1.74	S Clear	
POWER RANGE		
ADD POWER		
CYLINDER		
OTHER		
INVISIBLE MARKINGS - 15mm	-	
INVISIBLE MARKINGS - 18mm	-	

		TREATMENT				COATING
SuperLite™ 1.60	S Clear	Transiti@ns	<b>S</b> XTRActive	Vantage	Polarized	
POWER RANGE	-6.00 to +5.25	-6.00 to +5.25	-6.00 to +5.25		-6.00 to +5.25	
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50		+0.75 to +3.50	
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS - 15mm	16 250 FF-AS	76 250 FF-AS	X6 250 FF-AS		PZ6 250 FF-AS	
INVISIBLE MARKINGS - 18mm	16 250 FFA	76 250 FFA	X6 250 FFA		PZ6 250 FFA	

		TREATM	TREATMENT					
DLC™ TRIVEX™	S Clear	Transiti@ns	XTRActive	Polarized				
POWER RANGE	-5.00 to +4.00	-5.00 to +4.00	-5.00 to +4.00	-5.00 to +4.00				
ADD POWER	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50	+0.75 to +3.50				
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50				
OTHER		Gray/Brown	Gray	Gray/Brown				
INVISIBLE MARKINGS - 15mm	TX 250 FF-AS	TTX 250 FF-AS	XX 250 FF-AS	PTX 250 FF-AS				
INVISIBLE MARKINGS - 18mm	TX 250 FFA	TTX 250 FFA	XX 250 FFA	PTX OP OP 250 FFA				

			TREATMENT			COATING
SuperLite™ 1.67	S Clear	Transiti@ns SXTRActive		Vantage	Polarized	
POWER RANGE	-6.00 to +5.00 -6.00 to +5.00		-6.00 to +5.00		-6.00 to +5.00	
ADD POWER	+0.75 to +3.50 +0.75 to +3.50		+0.75 to +3.50 +0.75 t		+0.75 to +3.50	
CYLINDER	to -8.00	to -8.00 to -8.00			to -8.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS - 15mm	67 250 FF-AS	767 250 FF-AS	X67 250 FF-AS		PZ67	
INVISIBLE MARKINGS - 18mm	67 250 FFA	767 30 SD 250 FFA	X67 250 FFA		PZ67	

		TREAT	MENT			COATING
POLYPLUS™/ POLYCARBONATE	S Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE	-6.00 to +5.25					
ADD POWER	+0.75 to +3.50					
CYLINDER	to -7.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS - 15mm	PC 250 FF-AS	PT 250 FF-AS	PX 250 FF-AS	PV 250 FF-AS	PPZ 250 FF-AS	
INVISIBLE MARKINGS - 18mm	PC 250 FFA	250 FFA	PX 250 FFA	250 FFA	PPZ 250 FFA	





Zeiss AR Coating









## **PERFORMANCE> SPORT**



	TREATMENT							
CR-39	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized			
POWER RANGE								
ADD POWER								
BASE CURVE								
OTHER/COATING								
INVISIBLE MARKINGS								

	TREATMENT							
SuperLite™ 1.60	Clear	Transiti@ns	XTRActive	Vantage	Polarized			
POWER RANGE								
ADD POWER								
BASE CURVE								
OTHER/COATING								
INVISIBLE MARKINGS								

	TREATMENT						
SuperLite™ 1.67	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized		
POWER RANGE							
ADD POWER							
BASE CURVE							
OTHER/COATING							
INVISIBLE MARKINGS							

#### PRODUCT FEATURES:

☐ FREEFORM PAL ☐ FREEFORM SV CONVENTIONAL PAL EYEPOINT TECHNOLOGY®
 □ AS-WORN TECHNOLOGY®

- Recommended min fitting height is 16mm
- Cylinder to -6.00
- Prism to 4.00 Diopters

	TREATMENT
SuperLite™1.74	Clear
POWER RANGE	
ADD POWER	
BASE CURVE	
OTHER/COATING	
INVISIBLE MARKINGS	-

DLC™ TRIVEX™	TREATMENT							
	Clear	Transiti@ns <sup>-</sup>	XTRActive	Polarized				
POWER RANGE								
ADD POWER								
BASE CURVE								
OTHER/COATING								
INVISIBLE MARKINGS								

POLYPLUS™/ POLYCARBONATE	Clear	Transiti <b>©</b> ns	XTRActive	Vantage	Polarized
POWER RANGE	-4.00 to +2.00				-4.00 to +2.00
ADD POWER	+1.00 to +3.00				+1.00 to +3.00
BASE CURVE	8				8
OTHER/COATING	Piccolo®				Piccolo® Gray/Brown
INVISIBLE MARKINGS	<b>♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦</b>				<b>♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦ ♦</b>













SHAMIR **SINGLE VISION™**  PRESCRIPTOR ORDER CODE:

**GOLF SV** 

#### PRODUCT FEATURES:

☐ FREEFORM PAL ★ FREEFORM SV ☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

EYEPOINT TECHNOLOGY®
 AS-WORN TECHNOLOGY™

## NOTE:

• Prism to 4.00 Diopters

CR-39			TREATMENT			COATING
	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized	
POWER RANGE						
ADD POWER						
CYLINDER						
OTHER						
INVISIBLE MARKINGS						

	TREATMENT	COATING
SuperLite™1.74	Clear	
POWER RANGE		
ADD POWER		
CYLINDER		
OTHER	-	
INVISIBLE MARKINGS	-	

	TREATMENT					
SuperLite™ 1.60	S Clear	S Transiti@ns	<b>S</b> XTRActive	Vantage	Polarized	
POWER RANGE	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00		-6.00 to +6.00	
ADD POWER						
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS	₹ 16 \$\$ \$V	₹ 16 SV	₩ X6 SV		PZ6 SV	

		TREATMENT					
DLC™ TRIVEX™	S Clear	Transiti@ns	XTRActive	Polarized			
POWER RANGE	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00			
ADD POWER							
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50			
OTHER		Gray/Brown	Gray	Gray/Brown			
INVISIBLE MARKINGS	₹ TX SV	₹ TTX SV	<b>₹</b> XX SV	₹ PTX SV			

	TREATMENT					
SuperLite™ 1.67	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
POWER RANGE						
ADD POWER						
CYLINDER						
OTHER						
INVISIBLE MARKINGS						

	TREATMENT					COATING
POLYPLUS™/ POLYCARBONATE	Clear	Transitions	XTRActive	Vantage	Polarized	
POWER RANGE	-6.00 to +6.00					
ADD POWER						
CYLINDER	to -7.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS	₩ PC W SV	<b>V</b> PT SV	₹ PX SV	₩ PV SV	₩ PPZ ₩ SV	





Zeiss AR Coating



iCoat AR Coating







GOL-SIV-GUI-REF-092712

**AUTOGRAPH II SV ATTITUDE** 

#### PRODUCT FEATURES:

☐ FREEFORM PAL ☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

## NOTE:

• Prism to 4.00 Diopters

CR-39	TREATMENT					
	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized	
POWER RANGE	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	
ADD POWER						
CYLINDER	to -6.00	to -6.00	to -6.00	to -6.00	to -6.00	
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS	FF SA-15	FF SA-TR	FF SA-X5	FF SA-V5	FF SA-PZ	

	TREATMENT	COATING
SuperLite™1.74	Clear	
POWER RANGE		
ADD POWER		
CYLINDER		
OTHER		
INVISIBLE MARKINGS		

	TREATMENT					
SuperLite™ 1.60	S Clear	S Transiti@ns	<b>S</b> XTRActive	Vantage	Polarized	
POWER RANGE	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00		-6.00 to +6.00	
ADD POWER						
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS	FF SA-16	FF SA-T6	FF SA-X6		FF SA-PZ6	

DLC™ TRIVEX™	TREATMENT					
	S Clear	Transiti@ns	XTRActive	Polarized		
POWER RANGE	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00		
ADD POWER						
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50		
OTHER		Gray/Brown	Gray	Gray/Brown		
INVISIBLE MARKINGS	FF SA-TX	FF SA-TTX	FF SA-XX	FF SA-PTX		

			TREATMENT			COATING
SuperLite™ 1.67	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized	
POWER RANGE	-6.00 to +6.00	-6.00 to +6.00	-6.00 to +6.00		-6.00 to +6.00	
ADD POWER						
CYLINDER	to -8.00	to -8.00	to -8.00		to -8.00	
OTHER		Gray/Brown	Gray		Gray/Brown	•
INVISIBLE MARKINGS	FF SA-67	FF SA-T67	FF SA-X67		FF SA-PZ67	

		TREAT	MENT			COATING
POLYPLUS™/ POLYCARBONATE	Clear	Transitions	XTRActive	Vantage	Polarized	
POWER RANGE	-6.00 to +6.00					
ADD POWER						
CYLINDER	to -7.00					
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	•
INVISIBLE MARKINGS	FF SA-PC	FF SA-PT	FF SA-PX	FF SA-PV	FF SA-PPZ	
















# Autograph II **OFFICE**<sup>™</sup>

**AUTOGRAPH II OFFICE 16** 

## PRODUCT FEATURES:

☐ FREEFORM SV ☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

X EYEPOINT TECHNOLOGY®
 X AS-WORN TECHNOLOGY®

## NOTE:

- Recommended min fitting height is 16mm
- Prism to 4.00 Diopters

	TREATMENT					
CR-39	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized	
TOTAL NEAR POWER RANGE	-6.00 to +6.00					<b>(a)</b>
DYNAMIC REDUCTION	-0.75 to -2.25					
CYLINDER	to -6.00					
OTHER						
INVISIBLE MARKINGS	15 ••••••••••••••••••••••••••••••••••••					

		TREATMENT		COATING
SuperLite™1.74	Clear	⑤ Transiti⊚ns <sup>-</sup>	XTRActive	
TOTAL NEAR POWER RANGE				
DYNAMIC REDUCTION				
CYLINDER				
OTHER				
INVISIBLE MARKINGS				

	TREATMENT					
SuperLite™ 1.60	Olear	⑤ Transiti⊚ns	XTRActive	Vantage	Polarized	
TOTAL NEAR POWER RANGE	-6.00 to +8.00					
DYNAMIC REDUCTION	-0.75 to -2.25					
CYLINDER	to -7.00					
OTHER						
INVISIBLE MARKINGS	16 -175 FF0					

		TREAT	TREATMENT				
DLC™ TRIVEX™	© Clear	Clear		XTRActive			
TOTAL NEAR POWER RANGE							
DYNAMIC REDUCTION							
CYLINDER							
OTHER							
INVISIBLE MARKINGS							

	TREATMENT					
SuperLite™ 1.67	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
TOTAL NEAR POWER RANGE						
DYNAMIC REDUCTION						
CYLINDER						
OTHER						
INVISIBLE MARKINGS						

P0LYPLUS™/			TREATMENT			COATING
POLYCARBONATE Clear		⑤ Transiti⊚ns	XTRActive	Vantage	XTRActive	
TOTAL NEAR POWER RANGE	-6.00 to +8.00					
DYNAMIC REDUCTION	-0.75 to -2.25					
CYLINDER	to -7.00					
OTHER						•
INVISIBLE MARKINGS	PC -175 FF0					





Zeiss AR Coating









re LOX

PRESCRIPTOR ORDER CODE:

**RELAX 16** 

#### PRODUCT FEATURES:

☐ FREEFORM PAL ★ FREEFORM SV ☐ CONVENTIONAL PAL ☐ CONVENTIONAL SV

EYEPOINT TECHNOLOGY®
 □ AS-WORN TECHNOLOGY™

- Recommended min fitting height is 16mm
- Fatigue relief solution with .65 Add in lower part of lens
- Prism to 4.00 Diopters

	TREATMENT					
CR-39	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized	
POWER RANGE	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	-12.25 to +6.00	
ADD POWER						
CYLINDER	to -6.00	to -6.00	to -6.00	to -6.00	to -6.00	
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15	
INVISIBLE MARKINGS	15 RLX	TR TR RLX	X5 RLX	V5 RLX	PZ RLX	

	TREATMENT	COATING
SuperLite <sup>™</sup> 1.74	S Clear	
POWER RANGE		
ADD POWER		
CYLINDER		
OTHER		
INVISIBLE MARKINGS	-	

			TREATMENT			COATING
SuperLite™ 1.60	uperLite™ 1.60 See Clear		<b>S</b> XTRActive	Vantage	Polarized	
POWER RANGE	-14.00 to +8.00	-14.00 to +8.00	-14.00 to +8.00		-14.00 to +8.00	
ADD POWER						
CYLINDER	to -7.00	to -7.00	to -7.00		to -7.00	
OTHER		Gray/Brown	Gray		Gray/Brown	
INVISIBLE MARKINGS	<b>16 ₩</b> RLX	₩ T6 RLX	₩ X6 RLX		₩ PZ6 RLX	

	TREATMENT					
DLC™ TRIVEX™	S Clear	Transiti@ns	XTRActive	Polarized		
POWER RANGE	-13.25 to +6.00 -13.25 to +6.00		-13.25 to +6.00 -13.25 to +6.00			
ADD POWER						
CYLINDER	to -6.50	to -6.50	to -6.50	to -6.50		
OTHER		Gray/Brown	Gray	Gray/Brown		
INVISIBLE MARKINGS	₩ ₩ RLX	▼ TIX RLX	<b>₩</b> XX RLX	♥ PTX  RLX		

	TREATMENT						
SuperLite™ 1.67	S Clear	S Transiti@ns	S XTRActive	Vantage	Polarized		
POWER RANGE	-16.00 to +8.00	-16.00 to +8.00	-16.00 to +8.00		-16.00 to +8.00		
ADD POWER							
CYLINDER	to -8.00	to -8.00	to -8.00		to -8.00		
OTHER		Gray/Brown	Gray		Gray/Brown		
INVISIBLE MARKINGS	<b>★</b> 67 RLX	₩ ₩ T67	₩ X67 RLX		PZ67  RLX		

TM	TREATMENT						
POLYPLUS™/ POLYCARBONATE	Clear	S Transitions	XTRActive	Vantage	Polarized		
POWER RANGE	-14.00 to +8.00						
ADD POWER							
CYLINDER	to -7.00						
OTHER		Gray/Brown	Gray	Gray	Gray/Brown/G-15		
INVISIBLE MARKINGS	PC FLX	₹ PT RLX	PX RLX	₩ ₩ RLX	PPZ TP RLX		
















## **OCCUPATION**

# OFFICE

#### PRODUCT FEATURES:

☐ FREEFORM PAL
☐ FREEFORM SV
☒ CONVENTIONAL PAL
☐ CONVENTIONAL SV

X EYEPOINT TECHNOLOGY®
 □ AS-WORN TECHNOLOGY®

- Recommended min fitting height is 16mm lower and 10mm upper (Base 2 not available in 2.25DP.)
- Cylinder to -6.00

• Prism to 4.00 Diopter

NOTE:

 Base Curve selection is based on the Total Near Rx vs. the Standard Distance Rx.

CR-39	TREATMENT					
	Clear	Transiti@ns <sup>-</sup>	XTRActive	Vantage	Polarized	
TOTAL NEAR POWER RANGE	-6.00 to +6.00					
DYNAMIC REDUCTION	-0.75, -1.25, -1.75, -2.25					
BASE CURVE	2.5, 5, 7					
OTHER/COATING	Hard Coated/Uncoated					
INVISIBLE MARKINGS	) (					

SuperLite™1.74	TREATMENT
	Clear
TOTAL NEAR POWER RANGE	
DYNAMIC REDUCTION	
BASE CURVE	
OTHER/COATING	-
INVISIBLE MARKINGS	

SuperLite™ 1.60	TREATMENT					
	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
TOTAL NEAR POWER RANGE						
DYNAMIC REDUCTION						
BASE CURVE						
OTHER/COATING						
INVISIBLE MARKINGS						

DLC™ TRIVEX™	TREATMENT						
	Clear	Transiti@ns	XTRActive	Polarized			
TOTAL NEAR POWER RANGE							
DYNAMIC REDUCTION							
BASE CURVE							
OTHER/COATING							
INVISIBLE MARKINGS							

SuperLite™ 1.67	TREATMENT					
	Clear	Transiti@ns	XTRActive	Vantage	Polarized	
TOTAL NEAR POWER RANGE						
DYNAMIC REDUCTION						
BASE CURVE						
OTHER/COATING						
INVISIBLE MARKINGS						

POLYPLUS™/ POLYCARBONATE					
	Clear	Transiti@ns	XTRActive	Vantage	Polarized
TOTAL NEAR POWER RANGE	-3.00 to +6.00				
DYNAMIC REDUCTION	-0.75, -1.25, -1.75, -2.25				
BASE CURVE	5, 7				
OTHER/COATING	Hard Coated:				
INVISIBLE MARKINGS	) ( P 175				





Zeiss AR Coating



iCoat AR Coating

